Dane aktualne na dzień: 28-03-2024 10:25

Link do produktu: https://www.illuminations.pl/sys-t1-milight-1-kanalowa-magistrala-p-2308.html



SYS-T1 - MILIGHT - 1-kanałowa magistrala

Cena	**170,97 zł**
Dostępność	**Dostępny**
Czas wysyłki	**14 dni**
Numer katalogowy	**2308**
Producent	**Mi.Light**

Opis produktu

Nazwa produktu: 1-kanałowy kontroler hosta
Model nr: SYS-T1
Napięcie wejściowe: DC24V
Temperatura pracy: -20~60°C
Napięcie wyjściowe: DC24V
Prąd wyjściowy: maks. 15A
Moc wyjściowa: maks. 360 W
Odległość kontrolna: 30m


1-Channel Host Controller
2.4G Remote control, Smart phone APP Control(Need WiFi iBox);
Support DMX512 Control(Need Mi-Light DMX512 transmitter); Support
Amazon Alexa Voice Control(Need Mi-Light WiFi Remote)
Mi·Light
1-Channel Host Controller
2.4G RF
Model No.: SYS-T1
Input: DC24V
Working Temperature: -20~60℃
Output: DC24V
Output Current: Max 15A
Made in China
Indicator light
INPUT
V+
V-
OUTPUT
V+
V-
CHA
16 Millions
of colors to choose
Color temperature
2700~6500K
Dimmable
Saturation control
Auto-synchronization
Auto-transmitting function


Just compatible with Mi-Light SYS series products
Mi·Light
4-Channel Host Controller
2.4G RF
Model No.: SYS-T1
Input: DC24V
Working Temperature: -20~60°C
Output: DC24V
Output Current: Max 15A
Made in China
Indicator light
OUTPUT
DATA V- V+
INPUT
V+ V- V+ V-


Multiple functions
16 million colors change; Color temperature, brightness and saturation adjustable randomly
Mi·Light®
1-Channel Host Controller 2.4G RF
Model No.: SYS-T1
Input: DC24V
Working Temperature: -20~60℃
Output: DC24V
Output Current: Max 15A
Made in China
RoHS
Indicator light
INPUT
V+
V-
OUTPUT
V+
V-
DATA

Control never like this convenient

2.4GHz remote control, cell phone APP control, enjoy the convenient life bring by technology.
(*Need WiFi iBox for smartphone App control)



Compatible with




FUT089 FUT088 FUT092 B8 B4/T4 B0


Support Amazon Alexa Voice and DMX512 Control
Support DMX512 Control(Need Mi-Light DMX512 transmitter);
Support Amazon Alexa Voice Control(Need Mi-Light WiFi Remote)
Mi·Light
1-Channel Host Controller
amazon


Working status showed clearly
When the host controller is working, the indicating lamp blink;
When the host controller is not working, the indicating lamp lighting always.
Mi·Light®
1-Channel Host Controller 2.4G RF
Model No.: SYS-T1
Input: DC24V
Working Temperature: -20~60℃
Output: DC24V
Output Current: Max 15A
Made in China
RoHS
Indicator light
INPUT
V+
V-
OUTPUT
V+
V-
DATA


Auto-transmitting function

One Host Controller can transmit the signals from the remote control to another Host Controller within 30m, as long as there is a Host Controller within 30m, the remote control distance can be limitless.



Auto-synchronization function

Different controllers can work synchronously when they are started at different times, controlled by the same remote, under same dynamic mode and with same speed, and within 30m distance.



Connecting Terminal

① Power supply connecting terminal

② Light connecting terminal




PC housing

Adopt high quality PC housing, solid and durable




Mi·Light®
1-Channel Host Controller
2.4G RF
Model No.: SYS-T1
Input: DC24V
Working Temperature: -20~60℃
Output: DC24V
Output Current: Max 15A
Made in China
RoHS
Indicator light
INPUT
V+
V-
OUTPUT
V+
V-
DATA

Connection Diagram




Note: When using "SYS-T1 controller", you need to add "SYS-T2 1-channel signal amplifier" for below 3 situations.

1. Connecting over 50pcs lights.
2. Connected cable length over 300m.
3. Output power over 360W.

All connected lights to "SYS-T1 Controller" cannot be over 360W, otherwise, it will damage the controller.


27mm
115mm


48mm